



Document of Performance
According to Regulation (EU) 305/2011

Aduro 14		DoP No: 14 0014
Roomheater burning solid fuel <u>without</u> hot water supply.		
EN 16510-2-1:2022/A2:2004/AC:2007		
Aduro AS, Hasselager Allé 13D, DK-8260 Viby J. Adurofire.com / info@aduro.dk .		
System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.		
Rhein-Ruhr Feuerstätten Prüfstelle GmbH, Im Lipperfeld 34 b, D-46047 Oberhausen, notified body number: 1625 and Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300.		
performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report</u> : RRF- 40 13 3337 300-ELAB-1981-NS		
Declared performance		
Harmonized technical specification	EN 16510-2-1:2022/A2:2004/AC:2007	
Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	
Distance to combustible materials Distance marked with * is for installation with isolated pipe	Minimum distances, in mm rear = 150/*70 sides = 250 front = 1000 corner mounting = 100	
Risk of burning fuel falling out	Pass	
Emission of combustion products	CO[0,1 %]	
Surface temperature	Pass	
Electrical safety	NPD	
Cleanability	Pass	
Maximum water operating pressure	NPD	
Flue gas temperature at nominal heat output	T [246°C]	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output	6,5kW	
Room heating output	6,5 kW	
Water heating output	*** kW	
Energy efficiency	η [78 %]	

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS
Viby J, 21.08.2025