

Document of Performance
According to Regulation (EU) 305/2011

Aduro 17 Series Roomheater burning solid fuel <u>without</u> hot water supply. EN 16510-2-1:2022/A2:2004/AC:2007		DoP No: 17 0001
Aduro AS, Hasselager Allé 13D, DK-8260 Viby J. adurofire.com / info@aduro.dk		
System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.		
Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 1235. performed the determination of the pproduct type on the basis of type testing under system 3 and <u>issued test report</u> : 300-ELAB-2323-EN 300-ELAB-2323-NS		
Declared performance		
Harmonized technical specification	EN 16510-2-1:2022/A2:2004/AC:2007	
Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	
Distance to combustible materials	Minimum distances, in mm rear = 75 sides: - with side glass = 700 - without side glass = 400 front =1000	
Risk of burning fuel falling out	Pass	
Emission of combustion products Wood	CO[0.1 %]	
Surface temperature	Pass	
Electrical safety	NPD	
Cleanability	Pass	
Maximum water operating pressure	NPD	
Flue gas temperature at nominal heat output Wood	T [283°C]	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output Wood	7,0 kW	
Room heating output	7,0 kW	
Water heating output	"" kW	
Energy efficiency Wood	η [78 %]	

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS
Viby J, 21.08.2025

