

## Document of Performance According to Regulation (EU) 305/2011

## Aduro 19 Series, Asgård 8

DoP No: 19 0001

Roomheater burning solid fuel without hot water supply.

EN 16510-2-1:2022/A2:2004/AC:2007

Aduro AS, Hasselager Allé 13D, DK-8260 Viby J. Adurofire.com / info@aduro.dk

System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.

Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300.

Reein Ruhr Feuerstätten Prüfstelle GmbH, Im Lipperfeld 34 b, D-46047 Oberhausen, notified body number: 1625

performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report</u>: RRF- 40 16 4333 300-ELAB-1072-NS

Declared performance

Harmonized technical specification	EN 16510-2-1:2022/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm
Distance marked with * is for installation with isolated pipe	rear = 100
	sides = 300
	front = 850
Risk of burning fuel falling out	Pass
Emission of combustion products	CO[0,1 %]
Surface temperature	Pass
Electrical safety	NPD
Cleanability	Pass
Maximum water operating pressure	NPD
Flue gas temperature at nominal heat output	T [307°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	5,0 kW
Room heating output	5,0 kW
Water heating output	*** kW
Energy efficiency	$\eta$ [78 %]

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS

Viby J, 21.08.2025

CAL SU