

## **Document of Performance** According to Regulation (EU) 305/2011

Aduro 21 Series

DoP No: 21 0001

Roomheater burning solid fuel without hot water supply.

EN 16510-2-1:2022/A2:2004/AC:2007

Aduro AS, Hasselager Allé 13D, DK-8260 Viby J. Adurofire.com / info@aduro.dk

System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.

Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 1235

performed the determination of the product type on the basis of type testing under system 3 and issued test report:

300-ELAB-2613-NS

Declared performance

Harmonized technical specification	EN 16510-2-1:2022/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	-10
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm
Distance marked with * is for installation with isolated pipe	rear = 175
	sides = 650/ 500
	front =1200
Risk of burning fuel falling out	Pass
Emission of combustion products Wood	CO[0.1 %]
Surface temperature	Pass
Electrical safety	NPD
Cleanability	Pass
Maximum water operating pressure	NPD
Flue gas temperature at nominal heat output Wood	T [318°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output Wood	6,5 kW

6,5 kW

"" kW  $\eta$  [76 %]

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS

Viby J, 21.08.2025

Room heating output

Water heating output

**Energy efficiency Wood** 

Ish L 812